HOUSE SUBSTITUTE FOR

## SENATE BILL NO. 582

A bill to amend 1949 PA 300, entitled

"Michigan vehicle code,"

by amending section 719 (MCL 257.719), as amended by 2012 PA 80.

## THE PEOPLE OF THE STATE OF MICHIGAN ENACT:

Sec. 719. (1) A vehicle unloaded or with load shall not exceed
 a height of 13 feet 6 inches. The owner of a vehicle that collides
 with a lawfully established bridge or viaduct is liable for all
 damage and injury resulting from a collision caused by the height
 of the vehicle, whether the clearance of the bridge or viaduct is
 posted or not.

7 (2) Lengths described in this subsection shall be known as the
8 normal length maximum. Except as provided in subsection (3), the
9 following vehicles and combinations of vehicles shall not be

# S02995'11 (H-3)

1 operated on a highway in this state in excess of these lengths:

2 (a) Subject to subsection (8), any single vehicle: 40 feet; a
3 crib vehicle on which logs are loaded lengthwise of the vehicle:
4 42.5 feet; any single bus or motor home: 45 feet.

5

(b) Articulated buses: 65 feet.

(c) Notwithstanding any other provision of this section, a 6 combination of a truck and semitrailer or trailer, or a truck 7 tractor, semitrailer, and trailer, or truck tractor and semitrailer 8 9 or trailer, designed and used exclusively to transport assembled 10 motor vehicles or bodies, recreational vehicles, or boats: 65 feet. 11 Stinger-steered combinations: A COMBINATION OF A TRUCK AND 12 SEMITRAILER OR TRAILER, OR A TRUCK TRACTOR, SEMITRAILER, AND TRAILER, OR A TRUCK TRACTOR AND SEMITRAILER OR TRAILER DESIGNED AND 13 USED TO TRANSPORT BOATS FROM THE MANUFACTURER, OR A STINGER-STEERED 14 **COMBINATION:** 75 feet. The load on the combinations of vehicles 15 described in this subdivision may extend an additional 3 feet 16 17 beyond the front and 4 feet beyond the rear of the combinations of 18 vehicles. Retractable extensions used to support and secure the 19 load that do not extend beyond the allowable overhang for the front 20 and rear shall not be included in determining length of a loaded vehicle or vehicle combination. 21

(d) Truck tractor and semitrailer combinations: no overalllength, the semitrailer: 50 feet.

24

(e) Truck and semitrailer or trailer: 59 feet.

25 (f) Except as provided in subdivision (g), truck tractor,
26 semitrailer, and trailer, or truck tractor and 2 semitrailers: 59
27 feet.

# 2

S02995'11 (H-3)

(g) A truck tractor, semitrailer, and trailer, or a truck 1 tractor and 2 semitrailers, in which no semitrailer or trailer is 2 more than 28-1/2 feet long: 65 feet. This subdivision only applies 3 4 while the vehicle is being used for a business purpose reasonably 5 related to picking up or delivering a load and only if each 6 semitrailer or trailer is equipped with a device or system capable of mechanically dumping construction materials or dumping 7 construction materials by force of gravity. 8

9 (h) More than 1 motor vehicle, wholly or partially assembled,
10 in combination, utilizing 1 tow bar or 3 saddle mounts with full
11 mount mechanisms and utilizing the motive power of 1 of the
12 vehicles in combination: 55 feet.

(i) A recreational vehicle that has its own motive power, in combination with a trailer: 65 feet or, if the operator of the recreational vehicle has a group commercial motor vehicle designation on his or her operator's or chauffeur's license, 75 feet.

18 (3) Notwithstanding subsection (2), the following vehicles and
19 combinations of vehicles shall not be operated on a designated
20 highway of this state in excess of these lengths:

(a) Truck tractor and semitrailer combinations: no overall
length limit, the semitrailer 53 feet. All semitrailers longer than
50 feet shall have a wheelbase of 37.5 to 40.5 feet plus or minus
0.5 feet, measured from the kingpin coupling to the center of the
rear axle or the center of the rear axle assembly. A semitrailer
with a length longer than 50 feet shall not operate with more than
axles on the semitrailer. City, village, or county authorities

#### 3

# S02995'11 (H-3)

 $\operatorname{TLG}$ 

may prohibit stops of vehicles with a semitrailer longer than 50
 feet within their jurisdiction unless the stop occurs along
 appropriately designated routes, or is necessary for emergency
 purposes or to reach shippers, receivers, warehouses, and terminals
 along designated routes.

(b) Truck and semitrailer or trailer combinations: 65 feet, 6 7 except that a person may operate a truck and semitrailer or trailer designed and used to transport saw logs, pulpwood, and tree length 8 poles that does not exceed an overall length of 70 feet or a crib 9 vehicle and semitrailer or trailer designed and used to transport 10 11 saw logs that does not exceed an overall length of 75 feet. A crib vehicle and semitrailer or trailer designed to and used to 12 transport saw logs shall not exceed a gross vehicle weight of 13 14 164,000 pounds. A person may operate a truck tractor and semitrailer designed and used to transport saw logs, pulpwood, and 15 tree length wooden poles with a load overhang to the rear of the 16 semitrailer which does not exceed 6 feet if the semitrailer does 17 18 not exceed 50 feet in length.

19 (c) Notwithstanding subsection (4)(d), a truck tractor with a 20 log slasher unit and a log saw unit: no overall limit if the length 21 of each unit does not exceed 28-1/2 feet, or the overall length of 22 the log slasher unit and the log saw unit, as measured from the 23 front of the first towed unit to the rear of the second towed unit while the units are coupled together, does not exceed 58 feet. The 24 coupling devices of the truck tractor and units set forth in this 25 26 subdivision shall meet the requirements established under the motor 27 carrier safety act of 1963, 1963 PA 181, MCL 480.11 to 480.25.

# S02995'11 (H-3)

4

 $\operatorname{TLG}$ 

(d) Truck tractor and 2 semitrailers, or truck tractor,
 semitrailer, and trailer combinations: no overall length limit, if
 the length of each semitrailer or trailer does not exceed 28-1/2
 feet each, or the overall length of the semitrailer and trailer, or
 2 semitrailers as measured from the front of the first towed unit
 to the rear of the second towed unit while the units are coupled
 together does not exceed 58 feet.

8 (e) More than 1 motor vehicle, wholly or partially assembled,
9 in combination, utilizing 1 tow bar or 3 saddle mounts with full
10 mount mechanisms and utilizing the motive power of 1 of the
11 vehicles in combination: 75 feet.

12 (f) Truck tractor and lowboy semitrailer combinations: no maximum overall length, if the lowboy semitrailer does not exceed 13 14 59 feet, except as otherwise permitted under this subdivision. A lowboy semitrailer wheelbase shall not exceed 55 feet as measured 15 from the kingpin coupling to the center of the rear axle. A lowboy 16 17 semitrailer more than 59 feet in length shall not operate with more 18 than any combination of 4 axles on the lowboy unless an oversized 19 load permit is issued by the state transportation department or a 20 local authority with respect to highways under its jurisdiction. As used in this subdivision, "lowboy semitrailer" means a flatbed 21 22 semitrailer with a depressed section that has the specific purpose 23 of being lowered and raised for loading and unloading.

(4) The following combinations and movements are prohibited:
(a) A truck shall not haul more than 1 trailer or semitrailer,
and a truck tractor shall not haul more than 2 semitrailers or 1
semitrailer and 1 trailer in combination at any 1 time, except that

## S02995'11 (H-3)

TLG

5

a farm tractor may haul 2 wagons or trailers, or garbage and refuse
 haulers may, during daylight hours, haul up to 4 trailers for
 garbage and refuse collection purposes, not exceeding in any
 combination a total length of 55 feet and at a speed limit not to
 exceed 15 miles per hour.

6 (b) A combination of vehicles or a vehicle shall not have more
7 than 11 axles, except when operating under a valid permit issued by
8 the state transportation department or a local authority with
9 respect to a highway under its jurisdiction.

10 (c) Any combination of vehicles not specifically authorized11 under this section is prohibited.

(d) Except as provided in subsection (3)(c), a combination of semitrailers pulled by a truck tractor, unless each semitrailer uses a fifth wheel connecting assembly that conforms to the requirements of the motor carrier safety act of 1963, 1963 PA 181, MCL 480.11 to 480.25.

17 (e) A vehicle or a combination of vehicles shall not carry a
18 load extending more than 3 feet beyond the front of the lead
19 vehicle.

20 (f) A vehicle described in subsections (2)(e) and (3)(e)
21 employing triple saddle mounts unless all wheels that are in
22 contact with the roadway have operating brakes.

(5) All combinations of vehicles under this section shall
employ connecting assemblies and lighting devices that are in
compliance with the motor carrier safety act of 1963, 1963 PA 181,
MCL 480.11 to 480.25.

27

(6) The total gross weight of a truck tractor, semitrailer,

# S02995'11 (H-3)

and trailer combination or a truck tractor and 2 semitrailers
 combination that exceeds 59 feet in length shall not exceed a ratio
 of 400 pounds per engine net horsepower delivered to clutch or its
 equivalent specified in the handbook published by the society of
 automotive engineers, inc. (SAE), 1977 edition.

6 (7) A person who violates this section is responsible for a
7 civil infraction. The owner of the vehicle may be charged with a
8 violation of this section.

9 (8) The provisions in subsections (2) (a) and (3) (b)
10 prescribing the length of a crib vehicle on which logs are loaded
11 lengthwise do not apply unless 23 USC 127(d) is amended to allow
12 crib vehicles carrying logs to be loaded as described in this
13 section.

14

(9) As used in this section:

(a) "Designated highway" means a highway approved by the state
transportation department or a local authority with respect to a
highway under its jurisdiction.

18 (b) "Length" means the total length of a vehicle, or 19 combination of vehicles, including any load the vehicle is 20 carrying. Length does not include devices described in 23 CFR 21 658.16 and 23 CFR part 658, appendix d, 23 CFR 658.16 and 23 CFR 22 part 658, appendix d, as on file with the secretary of state are 23 adopted by reference. A safety or energy conservation device shall be excluded from a determination of length only if it is not 24 designed or used for the carrying of cargo, freight, or equipment. 25 26 Semitrailers and trailers shall be measured from the front vertical 27 plane of the foremost transverse load supporting structure to the

7

rearmost transverse load supporting structure. Vehicle components
 not excluded by law shall be included in the measurement of the
 length, height, and width of the vehicle.

4 (c) "Stinger-steered combinations" means a truck tractor and
5 semitrailer combination in which the fifth wheel is located on a
6 drop frame located behind and below the rearmost axle of the power
7 unit.